

DR-25-TW (2:1 shrink ratio)

Elastomer

Flexible, chemical, abrasion & diesel resistant

Applications

DR-25-TW is a 'Thin-Wall' version of DR-25 offering similar properties and is ideal for use where space and weight saving are important.

Features & Benefits

- 2:1 shrink ratio
- Excellent chemical & solvent resistance
- Excellent abrasion & mechanical protection
- Compatible with 'System 25' components
- Lightweight, thin wall

Operating Temperature

- From -75°C to +150°C

Installation

- Minimum shrink temperature +150°C
- Minimum full recovery +175°C



Specifications & Approvals

- VG-95343 Part 5 Type D
- VDE-0341 Part 9005
- RK 6008/2

Inside Diameter		Wall Thickness	Pack Size	Part Number
Minimum Supplied (mm)	Maximum Recovered (mm)	Nominal Recovered (mm)	Spools Only (SP)	
2.4	1.2	0.51	150m	DR-25-TW-3/32-0-SP
3.2	1.6	0.51	150m	DR-25-TW-1/8-0-SP
4.8	2.4	0.51	150m	DR-25-TW-3/16-0-SP
6.4	3.2	0.64	75m	DR-25-TW-1/4-0-SP
9.5	4.8	0.64	75m	DR-25-TW-3/8-0-SP
12.7	6.4	0.64	75m	DR-25-TW-1/2-0-SP
19.0	9.5	0.76	75m	DR-25-TW-3/4-0-SP
25.4	12.7	0.89	30m	DR-25-TW-1-0-SP
31.5	15.0	1.10	30m	DR-25-TW-1-1/4-0-SP
38.0	19.0	1.02	30m	DR-25-TW-1-1/2-0-SP

Notes:

- Wall thickness will be less if tubing recovery is restricted during shrinkage.
- All dimensions in millimetres, unless other stated for this and following page.

Part Number Example; DR-25-TW-3/4-0-SP 19mm inside diameter, black tubing, supplied on spools.

Ordering Information

Standard colour: 0=Black
 Size selection: The largest size that will recover snugly over the component(s).
 Standard packaging: Spools only - SP